## Compliance with relevant ASTM and ISO Standards as well as Industry Engineering specifications

Labino AB LED UV Lights	Built in White Light LED	UV Intensity at 38 cm (15") (μW/cm <sup>2</sup> )	COMPLIES WITH ASTM E3022-2018 Standard	COMPLIES WITH Rolls-Royce RRES 90061 Specification	COMPLIES WITH Airbus AITM6-1001 Testing Method	COMPLIES WITH Pratt & Whitney Requirements	COMPLIES WITH The Boeing Co Requirements	COMPLIES WITH ISO 3059-12 Standard	COMPLIES WITH USAF Requirements
GX SERIES – OVERHEAD LIGHT									
GX Orion REMOTE	1	1500-7000	✓	-	-	-	-	1	-
$\textbf{GX Orion} \ \cup \ \lor \ \& \ \ WH$	1	≈ 7 000	✓	-	-	✓	-	✓	-
<b>GX Orion</b> ∪V	-	≈ 4 500	✓	✓	✓	✓	✓	✓	1
BB 2.0 SERIES – HANDHELD LIGHT									
BB 2.0 Helios	-	≈ 9 000	✓	-	_	✓	-	✓	✓
BB 2.0 Ikaros	-	≈ 4 000	✓	✓	✓	✓	✓	✓	✓
BB 2.0 Artemis	-	≈ 22 000	✓	-	_	_	-	✓	-
MB 3.0 SERIES – HANDHELD LIG	нт								
Hercules Ex	_	≈ 4 000	✓	✓	✓	✓	✓	1	✓
MB 3.0 Zeus	✓	≈ 4 000	✓	✓	✓	✓	✓	✓	-
MB 3.0 Zeus with Athena	✓	≈ 4 000	✓	✓	✓	✓	✓	✓	-
MB 3.0 Hermes	-	≈ 4 000	✓	✓	✓	✓	✓	✓	✓
MB 3.0 Hermes with Athena	-	≈ 4 000	✓	✓	✓	✓	✓	✓	✓
MB 3.0 Selene	1	≈ 9 000	✓	-	-	✓	-	✓	-
MB 3.0 Selene with Athena	1	≈ 9 000	✓	-	_	✓	-	✓	-
MB 3.0 Atlas	-	≈ 9 000	✓	-	-	✓	-	✓	✓
MB 3.0 Atlas with Athena	-	≈ 9 000	✓	-	-	✓	-	✓	✓
UVG3/5 2.0 SERIES – FLASHLIGHT / HEADLIGHT									
UVG3 2.0 Spotlight	-	≈ 80 000	✓	-	-	-	-	✓	-
UVG3 2.0 Midlight	-	≈ 9 000	✓	_	_	✓	_	✓	✓
UVG3 2.0 Floodight	-	≈ 4 000	✓	✓	✓	✓	✓	✓	✓
<b>UVG5 2.0</b> Spotlight	0ptional	≈ 80 000	✓	-	-	-	_	✓	-
UVG5 2.0 Midlight	0ptional	≈ 9 000	✓	-	✓	✓	-	✓	✓
UVG5 2.0 Floodight	_	≈ 4 000	✓	<b>✓</b>	✓	✓	<b>/</b>	✓	✓

PLEASE NOTE: The above models are in compliance with the above ASTM and ISO standards as well as industry specifications as indicated on the table above irrespective of the power source (Battery or Mains).



**UV-A LED LAMPS**